MILLAGE ROGUE COLLECTION MANUAL INSTRUCTION




Cal. 5020.B



English User's Manual Battery type: 395 (diameter 9.5mm x 2.6mm / SR 927 SW) Accuracy: +20 / -10 seconds per month

In case your watch needs to be repaired or to raise claims under a guarantee, please contact the point of sales






Chronograph: Basic function (Start / Stop / Reset)


Start: Press push-button A.

- Stop: to stop the timing, press pushbutton A once more and read the 3 chronograph counters: 4h / 20 min / 38 sec
- Zero positioning:

 Press push-button B.

 (The 3 chronograph hands will be reset to their zero positions).






Chronograph: Intermediate or interval timing Example:

- Start: (start timing)
 Display interval:
 e.g. 10 minutes 10 seconds (timing continues in the background)
- Making up the measured time: (the 3 chronograph hands are quickly advanced to the ongoing measured time).
- Stop: (Final time is displayed)
 Reset: Reset: The 3 chronograph hands are returned to their zero position

Please note:
* Following , further intervals or intermediates can be displayed by pressing push-button B (display interval / make up measured time, ...)



Adjusting the chronograph hands to zero position

Example:
One or several chronograph hands are not in their correct zero positions and have to be adjusted (e.g. following a battery change).

- Pull out the crown to position III (all 3 chronograph hands are in their correct or incorrect zero position).
- Keep push-buttons A and B depressed simultaneously for at least 2 seconds (the centre stop-second rotates by 360° → corrective mode is activated).





Adjusting the minute counter hand and the hour counter hand (mechanical coupled)

Single step A 1 x short Continuous A long



Returning the crown to position I Termination of the chronograph hands adjustment (can be carried out at any time).

Second hand 0 @*Push the crown back into position I.

相 ₽₽

Push-hutton R

Setting the time

- Pull out the crown to position III (the watch stops).
- 2 Turn the crown until you reach the correct time 8:45.
- Please note:
 In order to set the time to the exact second,
 must be pulled out when the second
 hand is in position «60» (I).
 Once the hour and minute hands have been
 set, must be pushed back into position I
 at the exact second.







Setting the date (quick mode)

- Pull out the crown to position II (the watch continues to run).
- 2 Turn the crown until the correct date 1 appears.
- 3 Push the crown back into position I.

Please note: During the date changing phase between 9 PM and 12 PM; the date must be set to the date of the following day.

An extreme acceleration in setting the date with quick mode can induce a false date indication. The synchronization is re-established by setting the date from 01 till 31 (crown in position II).



Setting the date/time

- Date / time on the watch: 17 / 1:25 AM - Present date / time: 4 / 8:30 PM

Pull out the crown to position II (the watch continues to run).






Turn the crown until the correct date
4 appears.

6**Continue to turn the crown until the correct time 8:30 PM appears.





Please note:

* To set your watch to the exact second, please refer to the chapter entitled «setting the time».

** Please observe the AM/PM clock rhythm.